



Introduction

The Wattius wBMS-HX is a Battery Management System product family designed for applications up to **1.500 V** and provides reinforced isolation for all external interfaces according to IEC60664.

The wBMS-HX CMU12 is the 12-cell Cell Monitoring Unit of the HX family, **compatible with both wBMS-MX and wBMS-HX BMUs.**

The wBMS-HX products feature direct compliance with **IEC62619** and is pre-certified for **Functional Safety**, with a Compliance Report for IEC62061 **SIL2** and ISO13849-1 **Performance Level D** issued by a certified third-party testing entity.

Technical Specifications

Cell measurements (voltage & temperature)	Multiple cell chemistry. Extended internal redundancy and hardware integrity diagnostics. Open wire detection.
Cell voltage	5 - 12 cells. 0,1 - 4,5 Vdc. ± 1,5 mV cell voltage max total error.
Cell temperature	Up to 5 channels. Configurable NTC. ± 1°C cell temperature max total error.
Balancing	Configurable autonomous passive balancing strategy. 5 Ω per channel.
Isolation	1.500 V reinforced isolation (IEC60664).
Consumption	Active: < 10 mA Sleep: < 10 μA
Operating temperature range	-40 to +85 °C
Dimensions	L124 x W78 x H18 mm. 4x M4 mounting holes.
Connectors	Cell voltages and temperatures: Molex MicroFit. CMU-link communications: Molex MicroFit and/or RJ45.
Compliance	Functional Safety IEC62061 SIL2 and ISO13849-1 Performance Level D (Compliance Report from certified third-party available). Fully compatible with IEC62619, including 2023/1542/EU. EMC: 2024/30/EU RoHS: 2011/65/EU



W A + I U S

Wattius Battery Solutions

Camí de Can Bassa 6
08401 Granollers
Barcelona

+34 93 018 06 08
www.wattius.com
info@wattius.com